

Flexitallic®

novus™
a Flexitallic brand

Data / Specification Sheet • Novus 10

Novus 10 is a premium grade compressed sheet material based on carbon fibre with a high quality nitrile rubber binder system.



Service

A universal grade especially suitable for use under alkaline conditions with good steam resistance. It also possesses excellent creep resistance and is suitable for use with oils, fuels and refrigerants.

Approvals / Compliance

BS Specification 7531 Grade X

API 607 Fire Safe

TA-LUFT (in accordance with VDI Guideline 2440)

GL Approval 37702 - 12HH

Availability

Thickness range:
0.4mm to 6.0mm

Standard sheet sizes:

2.0m x 2.0m
2.0m x 1.5m
1.5m x 1.5m
1.5m x 1.0m

Standard roll sizes:

Up to a maximum size of 6.0m x 2.0m


Available with a fine mesh mild steel reinforcement: Novus 10 Metallic, can also be supplied with anti-stick finish.

Supplied as standard with anti-stick coating, can also be supplied with graphite coating.

Physical properties

Thickness		1.5mm
Density		1.57g/cc
Tensile Strength	ASTM F152	13MPa
Compression	ASTM F36	11%
Recovery	ASTM F36	62% min
Residual Stress	BS 7531 (300°C)	25MPa
Gas Leakage	BS 7531	<1cc/min
ASTM Oil 1	Thickness increase	1.0%
IRM 903 Oil	Thickness increase	2.5%
ASTM Fuel B	Thickness increase	2.5%

Novus 10 Pressure/Temperature Limits



- 1 Suitable subject to chemical compatibility.
- 2 Suitable in some cases but check your application requirements with Flexitallic.
- 3 Contact the Technical Team for application with higher temperatures and pressures. Applicable to 1.5mm and below.

The operating temperature of non-asbestos sheet material is related to the thickness of materials selected. Thinner materials give better temperature and pressure properties.

As the company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only, and without liability on the part of the company.