



BELDAM CROSSLEY LIMITED

P.O. Box 7, Hill Mill, Temple Rd, Bolton BL1 6PB
 Tel: (01204) 494711 Telex: 63149 Fax: (01204) 493203
 ISO 9001 Approved.

PRODUCT REFERENCE	PILOTPACK 5020	PRODUCT DATA SHEET NUMBER	112
PRODUCT DESCRIPTION	PILOTPACK 5020 is a firm crossplait constructed packing. It is fully impregnated with PTFE and silicone lubricant for initial bedding-in purposes. The high mechanical strength of the basic yarn makes the packing ideally suitable for high pressures.		
MATERIALS OF CONSTRUCTION	ARAMID FIBRE YARN PTFE DISPERSION SILICONE OIL		
COLOUR	YELLOW		
OPERATING CONDITIONS	TEMPERATURE RANGE	-200°C to +300°C	
	PRESSURE RANGE	Up to 300 bar	
	SPEED RANGE	Up to 20 m/s	
	pH RANGE	2 - 13 pH	
	SUITABLE MEDIA	Water, weak acids, weak alkalis, oils, abrasive slurries. Also suitable for use with foodstuffs.	
AVAILABILITY	3 mm to 25 mm sections. Larger sizes or specific lengths are available on request.		
TYPICAL APPLICATIONS	Pumps, valves, paper industry, refineries and chemical plants.		
NOTE	<p>Maximum temperature and pressure guides cannot necessarily be used simultaneously.</p> <p><i>This copy as dated supersedes all previous copies. We reserve the right to make changes to the product and datasheet without prior notification.</i></p> <p><i>As the application &/or conditions of use of this product are beyond BCL'S control, users should therefore satisfy themselves it is suitable for the intended purpose.</i></p> <p><i>Liability to users will only extend to the invoice value of the goods supplied, in respect of the above information.</i></p>		
AUTHORISED BY: M.NICHOLAS.		DATE: 13.12.2001	

